



**[www.radiohill.ch](http://www.radiohill.ch)**

Switzerland's first amateur radio internet remote base



Access Data Clubstation HB9Z

Website: [www.hb9z.ch](http://www.hb9z.ch)

IP-Address: 212.101.19.86

Skype-Address: hb9z\_remote

QTH: JN47HH

Sysop: Markus Schleutermann, HB9AZT

E-Mail: [hb9azt@bluewin.ch](mailto:hb9azt@bluewin.ch)

# 1. Zugangsmöglichkeit: via Browser

The screenshot shows a Microsoft Internet Explorer browser window titled "WebXCVR - Microsoft Internet Explorer". The address bar contains the URL "http://212.101.18.15:47881". The page content is a virtual radio control interface for station HB9AZT. At the top, it displays "HB9AZT--AVAILABLE" and the time "09:54 UTC". The interface includes a status bar with "PREAMP FAST", "RX-EQ", "TX-EQ 100w DIPOLE", and "TX DISABLED". The main display shows "20m USB" and a frequency of "14285.000". Below this is a control panel with various buttons and sliders, including "ATTEN", "PREAMP", "AGC", "N.R.", "NOTCH", "RX EQ", "LSB", "AM", "CW", "RPT", "ANT", "USB", "FM", "PSK", "HELP", "SPLIT", "A/B", "A=B", "TX MON", "TX EQ", "AMP", "VOX", "ANT TUNE", "PTT", "VOL", "RF", "SQ", "LO FILTER", "HI", "MIC", and "POWER". A numeric keypad is also present. At the bottom, there are fields for "TIME REMAIN" (0), "CALLSIGN" (GUEST), and "PASSWORD" (\*\*\*), along with "LOGON" and "AUDIO" buttons. The browser's status bar at the bottom shows "QTH JN47KK, 8-EL-LOGPER 30" and "Internet".

## 2. Zugangsmöglichkeit: Client-Software

HB9AZT - TS2000 Internet Remote Control 10:03 UTC

Setup Chat DX Cluster LogBook Memories IRB Monitor Info (Version 5.304.3)

**Frequency [kHz]** **3,669.000** LSB 3.0kHz Window 100W S-5

ATTEN OFF **PREAMP ON** 3669.000 TX

JN47KK, 8-EL-LOGPER 30M Tower, Carolina Windom 80m long. Doublet TURN MARQUEE OFF

**Rx** IF Band Pass 0.05kHz -- 3.00kHz Band **80m** **Tx** **TUNER ON** **Amp Avail**

AGC: **MedSlo** Tx Equ **H-Boost**

Noise Red: **Off** **Split** **Rx<-->Tx** =

Notch: **Off** Monitor **Off**

Rx Equ **H-Boost** CW Speed  16

RIT: **Off** Mic Gain  81

RF Gain:  100

AF Gain  60

Squelch  0

Copyright 1999-2005 Stan Schretter, W4MQ www.w4mq.com

**Push to Talk**

Session time remaining: 9997 minutes

In Use by HB9AZT (Rx/Tx) **LOGOFF** ReStart Radio **START AUDIO**

Select Remote **HB9AZT** Callsign **HB9AZT** Password **\*\*\*\*\***



[www.radiohill.ch](http://www.radiohill.ch)  
Switzerland's first amateur radio internet remote base

### Konfigurationstipps (1)

Webtransceiver-Clientprogramm

Setup/Logon Info:

Your Label: HB9Z

IRB Station: gewünschte Remote-Station eingeben, hier HB9Z

IP/URL: 212.101.19.86

Usercall: eigenes Call eingeben

Passwort: gemäss Sysop



**[www.radiohill.ch](http://www.radiohill.ch)**

Switzerland's first amateur radio internet remote base



Access Data Clubstation HB9Z

Website: [www.hb9z.ch](http://www.hb9z.ch)

IP-Address: 212.101.19.86

Skype-Address: hb9z\_remote

QTH: JN47HH

Sysop: Markus Schleutermann, HB9AZT

E-Mail: [hb9azt@bluewin.ch](mailto:hb9azt@bluewin.ch)

# 1. Zugangsmöglichkeit: via Browser

The screenshot shows a Microsoft Internet Explorer browser window titled "WebXCVR - Microsoft Internet Explorer". The address bar contains the URL "http://212.101.18.15:47881". The page content is a virtual radio control interface for the call sign "HB9AZT--AVAILABLE". The interface includes a status bar at the top with "09:54 UTC" and "TX DISABLED". The main display shows "20m USB" and a frequency of "14285.000". Below this is a control panel with various buttons and knobs, including "ATTEN", "PREAMP", "AGC", "N.R.", "NOTCH", "RX EQ", "LSB", "AM", "CW", "RPTR", "ANT", "USB", "FM", "PSK", "SPLIT", "A/B", "A=B", "TX MON", "TX EQ", "AMP", "VOX", "ANT TUNE", "PTT", "VOL", "RF", "SQ", "LO FILTER", "HI", "MIC", "POWER", "MENU", "RESET", and "HELP". At the bottom, there is a login section with fields for "TIME REMAIN" (0), "CALLSIGN" (GUEST), and "PASSWORD" (\*\*\*), along with "LOGON" and "AUDIO" buttons. The browser's status bar at the bottom shows "QTH JN47KK, 8-EL-LOGPER 30" and "Internet".

## 2. Zugangsmöglichkeit: Client-Software

HB9AZT - TS2000 Internet Remote Control 10:03 UTC

Setup Chat DX Cluster LogBook Memories IRB Monitor Info (Version 5.304.3)

**Frequency [kHz]** **3,669.000** LSB 3.0kHz Window 100W S-5

ATTEN OFF **PREAMP ON** 3669.000 TX  
JN47KK, 8-EL-LOGPER 30M Tower, Carolina Windom 80m long. Doublet TURN MARQUEE OFF

**Rx** IF Band Pass 0.05kHz -- 3.00kHz Band **80m** **Tx** **TUNER ON** **Amp Avail**

AGC: **MedSlo** Tx Equ **H-Boost**  
Noise Red: **Off** **Split** **Rx<-->Tx** =  
Notch: **Off** Monitor **Off**  
Rx Equ **H-Boost** CW Speed   
RIT: **Off** Mic Gain

RF Gain:   
AF Gain   
Squelch

Copyright 1999-2005 Stan Schretter, W4MQ www.w4mq.com  
Session time remaining: 9997 minutes

**In Use by HB9AZT (Rx/Tx)** **LOGOFF** ReStart Radio **START AUDIO**

Select Remote **HB9AZT** Callsign **HB9AZT** Password **\*\*\*\*\***



[www.radiohill.ch](http://www.radiohill.ch)

Switzerland's first amateur radio internet remote base



HB9AZT - TS2000 Internet Remote Control 06:31 UTC  
Setup Chat DX Cluster LogBook Memories IRB Monitor Info (Version 5.304.583)

Frequency (kHz) USB 3.0kHz Window 100W Heading: 000  
**14,313.000** S-4

ATTEN OFF **PREAMP ON** 14313.000 TX  
ive use! QTH JN47KK, 8-EL-LOGPER 30M Tower, Carolina Window 80m TURN MARQUEE OFF

**YOUR LABEL**

|        |  |  |
|--------|--|--|
| HB9AZT |  |  |
| HB9DUO |  |  |
| HB9Z   |  |  |
|        |  |  |
|        |  |  |
|        |  |  |
|        |  |  |
|        |  |  |
|        |  |  |
|        |  |  |

Click label to select for Edit

**Data for Label = HB9Z**

|                                  |                                  |              |
|----------------------------------|----------------------------------|--------------|
| <b>IRB STATION</b>               | <b>IP/URL</b>                    |              |
| HB9Z                             | 212.101.19.86                    |              |
| <b>USERCALL</b>                  | <b>PASSWD</b>                    | <b>AUDIO</b> |
| HB9AZT                           | XXXXX                            | SKYPE        |
| <input type="checkbox"/> AUTO IP | <input type="checkbox"/> NO-HOST |              |

DELETE ENTRY SAVE CLOSE

HB9AZT is Available LOGIN ReStart Radio START AUDIO

Select Remote **HB9AZT** Callsign **HB9AZT** Password \*\*\*\*\*

Konfigurationstipps (1)

Webtransceiver-Clientprogramm

Setup/Logon Info:

Your Label:HB9Z

IRB Station: gewünschte Remote-Station eingeben, hier HB9Z

IP/URL:212.101.19.86

Usercall: eigenes Call eingeben

Passwort: gemäss Sysop



**[www.radiohill.ch](http://www.radiohill.ch)**

Switzerland's first amateur radio internet remote base



Access Data Clubstation HB9Z

Website: [www.hb9z.ch](http://www.hb9z.ch)

IP-Address: 212.101.19.86

Skype-Address: hb9z\_remote

QTH: JN47HH

Sysop: Markus Schleutermann, HB9AZT

E-Mail: [hb9azt@bluewin.ch](mailto:hb9azt@bluewin.ch)

# 1. Zugangsmöglichkeit: via Browser

The screenshot shows a Microsoft Internet Explorer browser window titled "WebXCVR - Microsoft Internet Explorer". The address bar contains the URL "http://212.101.18.15:47881". The page content is a virtual radio control interface for station HB9AZT. At the top, it displays "HB9AZT--AVAILABLE" and the time "09:54 UTC". The interface includes a status bar with "PREAMP FAST", "RX-EQ", "TX-EQ 100w DIPOLE", and "TX DISABLED". The main display shows "20m USB" and a frequency of "14285.000". Below this is a control panel with various buttons and sliders, including "ATTEN", "PREAMP", "AGC", "N.R.", "NOTCH", "RX EQ", "LSB", "AM", "CW", "RPT", "ANT", "USB", "FM", "PSK", "HELP", "MENU", "RESET", "SPLIT", "A/B", "A=B", "TX MON", "TX EQ", "AMP", "VOX", "ANT TUNE", "PTT", "VOL", "RF", "SQ", "LO FILTER", "HI", "MIC", and "POWER". At the bottom, there is a login section with "TIME REMAIN 0", "CALLSIGN GUEST", "PASSWORD \*\*\*\*", and buttons for "LOGON" and "AUDIO". The browser's status bar at the bottom shows "QTH JN47KK, 8-EL-LOGPER 30" and "Internet".

## 2. Zugangsmöglichkeit: Client-Software

HB9AZT - TS2000 Internet Remote Control 10:03 UTC

Setup Chat DX Cluster LogBook Memories IRB Monitor Info (Version 5.304.3)

**Frequency [kHz]** **3,669.000** LSB 3.0kHz Window 100W S-5

ATTEN OFF **PREAMP ON** 3669.000 TX

JN47KK, 8-EL-LOGPER 30M Tower, Carolina Windom 80m long. Doublet TURN MARQUEE OFF

**Rx** IF Band Pass 0.05kHz -- 3.00kHz Band **80m** **Tx** **TUNER ON** **Amp Avail**

AGC: **MedSlo** Tx Equ **H-Boost**

Noise Red: **Off** **Split** **Rx<-->Tx** =

Notch: **Off** Monitor **Off**

Rx Equ **H-Boost** CW Speed

RIT: **Off** Mic Gain

RF Gain:

AF Gain

Squelch

Copyright 1999-2005 Stan Schretter, W4MQ www.w4mq.com

Push to Talk

Session time remaining: 9997 minutes

In Use by HB9AZT (Rx/Tx) **LOGOFF** ReStart Radio **START AUDIO**

Select Remote **HB9AZT** Callsign **HB9AZT** Password **\*\*\*\*\***



[www.radiohill.ch](http://www.radiohill.ch)

Switzerland's first amateur radio internet remote base



HB9AZT - TS2000 Internet Remote Control 06:31 UTC  
Setup Chat DX Cluster LogBook Memories IRB Monitor Info (Version 5.304.583)

Frequency (kHz) USB 3.0kHz Window 100W Heading: 000  
**14,313.000** S-4

ATTEN OFF **PREAMP ON** 14313.000 TX  
ive use! QTH JN47KK, 8-EL-LOGPER 30M Tower, Carolina Window 80m TURN MARQUEE OFF

**YOUR LABEL**

|        |  |  |
|--------|--|--|
| HB9AZT |  |  |
| HB9DUO |  |  |
| HB9Z   |  |  |
|        |  |  |
|        |  |  |
|        |  |  |
|        |  |  |
|        |  |  |
|        |  |  |

Click label to select for Edit

**Data for Label = HB9Z**

|                                  |                                  |              |
|----------------------------------|----------------------------------|--------------|
| <b>IRB STATION</b>               | <b>IP/URL</b>                    |              |
| HB9Z                             | 212.101.19.86                    |              |
| <b>USERCALL</b>                  | <b>PASSWD</b>                    | <b>AUDIO</b> |
| HB9AZT                           | XXXXX                            | SKYPE        |
| <input type="checkbox"/> AUTO IP | <input type="checkbox"/> NO-HOST |              |

DELETE ENTRY SAVE CLOSE

HB9AZT is Available LOGIN ReStart Radio START AUDIO

Select Remote **HB9AZT** Callsign **HB9AZT** Password \*\*\*\*\*

Konfigurationstipps (1)

Webtransceiver-Clientprogramm

Setup/Logon Info:

Your Label:HB9Z

IRB Station: gewünschte Remote-Station eingeben, hier HB9Z

IP/URL:212.101.19.86

Usercall: eigenes Call eingeben

Passwort: gemäss Sysop